




Project: Date:

Prepared By:

Comments:



FEATURES

- Built to last with durable steel construction and a baked enamel finish
- High performance LEDs
- Accommodates a fixture-mounted sensor for added energy savings and convenience

APPLICATIONS

- Cold Storage Facilities
- Commercial
- Gyms
- Industrial
- Parking Areas
- Retail
- Warehouses

CERTIFICATIONS

- DLC Premium

... Visit our website for more information.

ELECTRICAL

Part Number: HB2W1250UPC

Warranty: 5 years

Kelvin Temperature (CCT): 5000K

Wattage: 89

Lumens: 11,400

Efficacy: 128

CRI: 83

Dimmable: 0-10V

Input Voltage: 120/277V

Certifications: DLC Premium

DLC Listed: DLCP

Expected Life: 50000

Max. Ambient Temperature 40°C

Min. Ambient Temperature 0°C

Power Factor: 0.99

THD: YES

SPECIFICATIONS

Weight: 9.7 lbs

Length: 23.75

Product Height: 3.75

Product Width: 12.75

Beam Angle: 110

Lens: Plastic





Project: Date:


Prepared By:

Comments

Photometrics

ZONAL LUMEN SUMMARY

ZONE	LUMENS	% LUMINAIRE
0-30	3,380.6	30.2%
0-40	5,499.7	49.2%
0-60	9,308.2	83.2%
60-90	1,874.7	16.8%
70-100	718.5	6.4%
90-120	0.000	0%
0-90	11,182.9	100%
90-180	0.000	0%
0-180	11,182.9	100%



Highlights

- Built to last with durable steel construction and a baked enamel finish
- High performance LEDs
- Accommodates a fixture-mounted sensor for added energy savings and convenience

